
Ferrurles for 1SN R1AT Braided Hose Fittings



00110

SOCKET FOR 1SN / R1AT HOSE

PART NO.		HOSE SIZE			DIMENSIONS				
		DN	DASH		L	D	d		
00110-03AZ		5	03		23	18.5	12.6		
00110-04AZ *		6	04		27.4	21	14		
00110-05AZ *		8	05		28	21.5	15.6		
00110-06AZ *		10	06		30	24.3	18		
00110-08AZ *		12	08		34	28	21.5		
00110-10AZ *		16	10		37	31.3	24.5		
00110-12AZ *		20	12		42	35.5	28.7		
00110-16AZ *		25	16		51	43.5	36.3		
00110-20Z *		32	20		59	52	45		
00110-24Z *		40	24		74	58	51.5		
00110-32Z *		50	32		78	72	65		

1. Part no. marked with "*" is recommended.

2. Matched with braid fitting and ISO 1436 1SN & R1ATS, GB/T 3683 1SN & R1ATS, EN 853 1SN, SAE J517 100R1AT braid hose, and no-skive needed.

3. Material options for socket.

Socket material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	00110-08AZ
304 stainless steel	SR	00110-08ASR
316L stainless steel	SV	00110-08ASV
316Ti stainless steel	SY	00110-08ASY

4. Plating options and performance for carbon steel socket

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	00110-08AZ	96	360
Durakote plating	ZD	00110-08AZD	360	720
Zinc-nickel plating	ZN	00110-08AZN	1000	-